

temperature measurement

resistance thermometer WTR 495

features

- modular resistance thermometer for food industry
- adaptable with sleeve socket and process connections (see accessories)
- process connection thread G1/2"
- short reaction time without reduced measuring point
- temperature resistance PT100 directly constructed in protective fitting
- electrical connection with M12-plug (connections see accessories)
- optional with programmable measuring transducer (same program kit like at KMU100), output 4-20mA 2-wire
- specials on request

technical specifications

- protective fitting made of stainless steel V4A 1.4404 (316L) resp. V4A 1.4571
- temperature range: -50 °C to +150 °C (extended ranges on request)
- power supply at option measuring transducer 10...35VDC
- tightening torque max. 10-15 Nm
- tighten the sensor only at the wrench area

product benefits

The WTR 495 is a temperature sensor for the food industry in very compact design. It impresses by its food safe as well as conical or spherical measuring tip, which is aseptically adapted by means of the welding sleeve (ZEM 150 or KEM 150). The additional PEEK ring (temperature decoupling) on the measuring tip counteracts falsifying temperature influences of container walls or container environments. Thanks to its design, the sensor is ideally suited for applications in tanks or containers with agitators or similar.



WTR 495-9-XR...-1A-PMU



WTR 495-9-XR...-1A




WTR 495-9-XS...-1A-PMU


picture will follow shortly

WTR 495-9-XS...-1A

pin assignment



M12 plug with PMU




M12 plug (only PT100)


technical drawing

spherical measuring tip (XR)



without PMU



conical measuring tip (XS)



with PMU



temperature measurement

order-code WTR 495...

order example: WTR 495-9-XS-1A-PMU (0-100 °C)

kind of connection

-9 compact construction, directly with M12 plug, protection class IP69K

mounting type

-XR spherical measuring point, thermal decoupled
 -XS tapered measuring point, thermal decoupled

type of sensor and tolerance

-1A 1xPT100 classe A
 -KX other types of sensor and tolerance on customer's request

optional

-PMU with programmable measuring transducer (temperature ranges on request on preadjustment please specify)

accessories

welding sleeves

-99-000191 KEM 150, welding sleeve, bullet, for G1/2" sealing system, diameter 35m,
 hygienic process adaption
 -99-000193 ZEM 150, welding sleeve, cylinder, for G1/2" sealing system, diameter 30mm,
 hygienic process adaptation

M12-connection wires

-101090 connection cable M12 angled, 4-pole, 5m PVC cable, grey
 -101087 connection cable M12 straight, 4-pole, 5m PVC cable, grey

Other lengths available on request.

For more accessories, see accessories data sheet.